


boby@innometrics.com.cn

(www.innorfid.com.cn

RFID LABELS







Specification:

Тад Туре:	RFID Labels
Chip:	NXP UCODE 9
Memory:	EPC 96bits, TID 48bits, User 0bits
Material:	Printable paper, PET, PP
Color:	White, CMYK color available
Antenna dimension:	Diameter 27mm
Label dimension:	Diameter 30mm
Protocol:	EPC Class1 Gen2, ISO18000-6C
Operating Frequency:	860-960Mhz
Read Range:	5-15M (may change based different readers and environment)
Adhesive:	Permanent adhesive

Model:INNO-LBNXP-U9D30



This is wet inlay/label with diameter 25mm antennas. with NXP UCODE 9 chip, it is optimized for next generation of high memory and high performance. the circular shape makes it very Easy & Quick to apply, especially when trying to align the label to the corner sides of the object, making it ideal for deployment across a multitude of applications.

•••• Key Features:

- Round antenna design.
- Worldwide operation in all RFID UHF bands (860-960 MHz).
- ISO/IEC 18000-6C compliance.
- EPC memory programmable
- Customization available with paper label
- Batch reading

Mounting Methods:	Self-Adhesive
Data storage:	up to 10 years
Re-write:	100,000 times
Warranty:	1 year
Operating Temp:	-40°C~+85°C
Weight:	0.02g
Core Inner Diameter:	76mm
Packing Detail:	2500pcs/Reel
Printers supported:	ZEBRA: ZT400 Series, ZT600 Series, ZD500R, ZE500R, etc. SATO: CT4-LX Series, CL4NX, CL4NX Plus, CL6NX Plus, S84-ex,etc
Applications:	Apparel hangtag, Foot wear management, Asset management tracking, etc.

Member Of Inno Groups



