

boby@innometrics.com.cn

www.innorfid.com.cn

INK-JET PROXIMITY CARD




Model:INNO-EMCARD-INKJET

Profile

This proximity card is developed based on passive Ink-Jet technology and RFID Technology of Low frequency (125Khz), which supports Ink-Jet printer and ISO 18000 protocol. Widely used in a lot of industries, like security and access control system, Employee management system, Hotel management system, etc.

STRUCTURE



•••• Key Features:

- Milk white PVC material, which satisfies most people in the world.
- Printable surface for branded Ink-Jet printers of HP, Epson, Canon, etc.
- Price competitive with all other card technologies.
- External number for easy identification and access control.
- Customized shapes, sizes and pre-printed artworks available.
- High-quality ink-jet coating, waterproof.
- Double sided high resolution printing, quickly dry.

Specification:

Physical specification	
Material	PVC
Size	CR80 (85.6*54mm), customized size available
Thickness	0.86 mm
Color	Milk white
Available Crafts	Silk-screen, spray code, number printing (ink-jet printing or laser engraving), etc.
Available Crafts	Ink-jet coating
Performance Specification	
Frequency	125Khz
Available chips	Tk4100, EM4200, EM4305, T5577, CET5577
Read/Write range	1-10CM
Protocol supported	ISO 18000

Environmental specification	
Working Temperature	-10 °C ~ 50 °C
Storage Temperature	-25 °C ~ 50 °C
Performance specification	
Packing details	
Gross weight	0.0068kgs/pcs
Destaur	400 / 1 000 // 5000 / 1

Package	100pcs/pack, 200pcs/box,5000pcs/carton
Carton size	52*24.5*32cm