


boby@innometrics.com.cn

www.innorfid.com.cn

DUAL FREQUENCY CARD (EM+UHF)




Model:INNO-DLCARD-EU

Profile

This dual frequency card is developed based on passive RFID Technology of EM (125Khz), and UHF (860-960Mhz), which support ISO18000 and ISO18000-6C/EPC Gen2 protocol. Widely used for payment and access control.

STRUCTURE



Key Features:

- Milk white PVC material, which satisfies most people in the world.
- Printable surface for branded printers of Zebra, Datacard, Evolis, Fargo, etc.
- Price competitive with all other card technologies.
- External number for easy identification and access control.
- Customized shapes, sizes and pre-printed artworks available.

Specification:

Physical specification	
Material	PVC/PET
Size	85.6 *54mm (customized size available)
Thickness	0.86mm
Color	Milk white (pre-printed and transparent available)
Available Crafts	silk-screen, spray code, number printing (inkjet printingor laser engraving), etc.
Performance Specifi	cation
Frequency	125Khz + 860-960Mhz
Available chips	EM (125Khz): TK4100, EM4200, EM4305, T5577, etc. UHF (860-960MHz): Alien H3/H9, NXP U8/U9, etc.
Read/Write range	EM (125Khz): 1-10CM UHF (860-960Mhz): 1-15M

Environmental Specification	
Working Temperature	-10 °C ~ 50 °C
Storage Temperature	-25 °C ~ 50 °C
Packing details	
Gross weight	0.0068kgs/pcs
Package	100pcs/pack, 200pcs/box,5000pcs/carton
Carton size	52*24.5*32cm

