


boby@innometrics.com.cn

(www.innorfid.com.cn

RFID LABELS







Specification:

Тад Туре:	RFID Labels
Chip:	NXP UCODE 9
Memory:	EPC 96bits, TID 48bits, User 0bits
Material:	Printable paper, PET, PP
Color:	White, CMYK color available
Antenna dimension:	95*8mm
Label dimension:	98*12mm
Protocol:	EPC Class1 Gen2, ISO18000-6C
Operating Frequency:	860-960Mhz
Read Range:	5-15M (may change based different readers and environment)
Adhesive:	Permanent adhesive

Model:INNO-LBNXP-U99812



This is wet inlay/label with 95*8mm antennas. With NXP UCODE 9 chip, it is optimized for next generation of high memory and high performance. It may be attached on the individual cases, item levels or pallets, each RFID label is serialized, which is very easy for identify and inventory or warehouse management, etc.

•••• Key Features:

- Narrow antenna design.
- Worldwide operation in all RFID UHF bands (860-960 MHz).
- ISO/IEC 18000-6C compliance.
- EPC memory programmable
- Customization available with paper label
- Batch reading

Mounting Methods:	Self-Adhesive
Data storage:	up to 10 years
Re-write:	100,000 times
Warranty:	1 year
Operating Temp:	-40°C~+85°C
Weight:	0.02g
Core Inner Diameter:	76mm
Packing Detail:	2500pcs/Reel
Printers supported:	ZEBRA: ZT400 Series, ZT600 Series, ZD500R, ZE500R, etc. SATO: CT4-LX Series, CL4NX, CL4NX Plus, CL6NX Plus, S84-ex,etc
Applications:	Apparel hangtag, Foot wear management, Asset management tracking, etc.

Member Of Inno Groups



